

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/363082458>

US 11357620 – Exchangeable Optics and Therapeutics

Patent · August 2022

CITATIONS

0

READS

39

1 author:



Bradley Barnett

California LASIK & Eye

94 PUBLICATIONS 2,036 CITATIONS

SEE PROFILE

Some of the authors of this publication are also working on these related projects:




SARS-CoV-2 Ocular Transmission [View project](#)



The impact of ocular surface disease on preoperative measurements [View project](#)

*United
States
of
America*



To Promote the Progress

of Science and Useful Arts

The Director

of the United States Patent and Trademark Office has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this United States

Patent

grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America, and if the invention is a process, of the right to exclude others from using, offering for sale or selling throughout the United States of America, products made by that process, for the term set forth in 35 U.S.C. 154(a)(2) or (c)(1), subject to the payment of maintenance fees as provided by 35 U.S.C. 41(b). See the Maintenance Fee Notice on the inside of the cover.

Katherine Kelly Vidal

DIRECTOR OF THE UNITED STATES PATENT AND TRADEMARK OFFICE

Maintenance Fee Notice

If the application for this patent was filed on or after December 12, 1980, maintenance fees are due three years and six months, seven years and six months, and eleven years and six months after the date of this grant, or within a grace period of six months thereafter upon payment of a surcharge as provided by law. The amount, number and timing of the maintenance fees required may be changed by law or regulation. Unless payment of the applicable maintenance fee is received in the United States Patent and Trademark Office on or before the date the fee is due or within a grace period of six months thereafter, the patent will expire as of the end of such grace period.

Patent Term Notice

If the application for this patent was filed on or after June 8, 1995, the term of this patent begins on the date on which this patent issues and ends twenty years from the filing date of the application or, if the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121, 365(c), or 386(c), twenty years from the filing date of the earliest such application ("the twenty-year term"), subject to the payment of maintenance fees as provided by 35 U.S.C. 41(b), and any extension as provided by 35 U.S.C. 154(b) or 156 or any disclaimer under 35 U.S.C. 253.

If this application was filed prior to June 8, 1995, the term of this patent begins on the date on which this patent issues and ends on the later of seventeen years from the date of the grant of this patent or the twenty-year term set forth above for patents resulting from applications filed on or after June 8, 1995, subject to the payment of maintenance fees as provided by 35 U.S.C. 41(b) and any extension as provided by 35 U.S.C. 156 or any disclaimer under 35 U.S.C. 253.

(12) **United States Patent**
Barnett

(10) **Patent No.:** **US 11,357,620 B1**
(45) **Date of Patent:** **Jun. 14, 2022**

- (54) **EXCHANGEABLE OPTICS AND THERAPEUTICS**
- (71) Applicant: **California LASIK & Eye, Inc.**, Sacramento, CA (US)
- (72) Inventor: **Bradley P. Barnett**, Sacramento, CA (US)
- (73) Assignee: **CALIFORNIA LASIK & EYE, INC.**, Sacramento, CA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

4,409,691 A	10/1983	Levy
4,435,856 A	3/1984	L'Esperance
4,494,254 A	1/1985	Lopez
4,681,102 A	7/1987	Bartell
4,693,245 A	9/1987	Pao
4,741,330 A	5/1988	Hayhurst
4,769,035 A	9/1988	Kelman
4,816,031 A	3/1989	Pfaff
4,828,558 A	5/1989	Kelman
4,842,601 A	6/1989	Smith
4,878,910 A	11/1989	Koziol et al.
4,932,971 A	6/1990	Kelman
4,950,272 A	8/1990	Smirmaul
4,950,289 A	8/1990	Krasner
4,960,418 A	10/1990	Tennant

(Continued)

- (21) Appl. No.: **17/471,496**
- (22) Filed: **Sep. 10, 2021**

FOREIGN PATENT DOCUMENTS

AU	2018271403 B2	2/2019
AU	2017345731 B2	10/2019

(Continued)

- (51) **Int. Cl.**
A61F 2/16 (2006.01)
A61L 27/54 (2006.01)
- (52) **U.S. Cl.**
CPC *A61F 2/1648* (2013.01); *A61F 2/1624* (2013.01); *A61F 2/1602* (2013.01); *A61F 2002/1682* (2015.04); *A61F 2002/16902* (2015.04); *A61L 27/54* (2013.01)
- (58) **Field of Classification Search**
CPC *A61F 2/1602*; *A61F 2/1648*; *A61F 2002/16902*; *A61L 27/54*
See application file for complete search history.

Primary Examiner — Javier G Blanco
(74) Attorney, Agent, or Firm — Talem IP Law, LLP

(56) **References Cited**



U.S. PATENT DOCUMENTS

3,937,222 A	2/1976	Banko
4,168,547 A	9/1979	Konstantinov et al.
4,298,996 A *	11/1981	Barnet <i>A61F 2/16</i> 623/6.43

(57) **ABSTRACT**

An exchangeable optics system includes an intraocular base that can be fixed within an eye. The intraocular base includes one or more couplers and a supporting structure. The one or more couplers releasably couple to an exchangeable optic or therapeutic and can include magnetic material. The supporting structure can include haptics and a main structure that physically supports the exchangeable optic or the therapeutic that is coupled via the one or more couplers. In some cases, the intraocular base can include a fixed lens within or on the main structure. The exchangeable optic can include corresponding one or more couplers, which may be formed of magnetic material. The therapeutic can be in the form of a magnetic particle.

6 Claims, 15 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,026,396	A	6/1991	Darin	7,220,278	B2	5/2007	Peyman	
5,098,444	A	3/1992	Feaster	7,223,288	B2	5/2007	Zhang et al.	
5,123,905	A	6/1992	Kelman	7,238,201	B2	7/2007	Portney et al.	
5,133,747	A	7/1992	Feaster	7,300,464	B2	11/2007	Tran	
5,147,369	A	9/1992	Wagner	7,316,713	B2	1/2008	Zhang	
5,152,788	A	10/1992	Isaacson et al.	7,455,691	B2	11/2008	Feingold et al.	
5,201,762	A	4/1993	Hauber	7,582,113	B2	9/2009	Terwee	
5,222,981	A	6/1993	Werblin	7,591,849	B2	9/2009	Richardson	
5,304,182	A	4/1994	Rheinish et al.	7,645,299	B2	1/2010	Koziol	
5,323,788	A	6/1994	Silvestrini et al.	7,662,179	B2	2/2010	Sarfarazi	
5,354,335	A	10/1994	Lipshitz et al.	7,727,277	B2	6/2010	Aharoni et al.	
5,358,520	A	10/1994	Patel	7,780,729	B2	8/2010	Nguyen et al.	
5,378,475	A	1/1995	Smith et al.	7,857,850	B2	12/2010	Mentak et al.	
5,410,375	A	4/1995	Fiala	7,871,437	B2	1/2011	Hermans et al.	
5,417,369	A	5/1995	Lipson	7,918,886	B2	4/2011	Aharoni et al.	
5,507,805	A	4/1996	Koeniger	7,985,253	B2	7/2011	Cumming	
5,578,081	A	11/1996	McDonald	7,993,399	B2	8/2011	Peyman	
5,616,120	A	4/1997	Andrew et al.	7,998,198	B2	8/2011	Angelopoulos et al.	
5,628,795	A	5/1997	Langerman	8,012,204	B2	9/2011	Weinschenk, III et al.	
5,728,155	A	3/1998	Anello et al.	8,034,106	B2	10/2011	Mentak et al.	
5,769,890	A	6/1998	McDonald	8,034,107	B2	10/2011	Stenger	
5,814,103	A	9/1998	Lipshitz et al.	8,034,108	B2	10/2011	Bumbalough	
5,824,074	A	10/1998	Koch	8,062,361	B2	11/2011	Nguyen et al.	
5,860,985	A	1/1999	Anschutz	8,066,768	B2	11/2011	Werblin	
5,876,442	A	3/1999	Lipshitz et al.	8,137,399	B2	3/2012	Glazier et al.	
5,895,422	A	4/1999	Hauber	8,167,941	B2	5/2012	Boyd et al.	
5,902,598	A	5/1999	Chen et al.	8,187,325	B2	5/2012	Zadno-Azizi et al.	
5,928,283	A	7/1999	Gross et al.	8,197,541	B2	6/2012	Schedler	
5,944,725	A	8/1999	Cicenas et al.	8,273,123	B2	9/2012	Ben Nun	
5,968,094	A	10/1999	Werblin et al.	8,287,593	B2	10/2012	Portney	
6,027,531	A	2/2000	Tassignon	8,377,124	B2	2/2013	Hong et al.	
6,066,171	A	5/2000	Lipshitz et al.	8,377,125	B2	2/2013	Kellan	
6,090,141	A	7/2000	Lindstrom	8,480,734	B2	7/2013	Kellan et al.	
6,113,633	A	9/2000	Portney	8,728,158	B2	5/2014	Whitsett	
6,197,057	B1	3/2001	Peyman et al.	8,758,434	B2	6/2014	Scott	
6,197,058	B1	3/2001	Portney	8,900,300	B1	12/2014	Wortz	
6,228,113	B1	5/2001	Kaufman	9,078,744	B2	7/2015	Van Noy	
6,231,603	B1	5/2001	Lang et al.	9,339,375	B2	5/2016	Lee et al.	
6,261,321	B1	7/2001	Kellan	9,358,103	B1	6/2016	Wortz et al.	
6,277,146	B1	8/2001	Peyman et al.	9,364,316	B1	6/2016	Kahook et al.	
6,280,471	B1	8/2001	Peyman et al.	9,414,907	B2	8/2016	Wortz et al.	
6,358,280	B1	3/2002	Herrick	9,486,311	B2	11/2016	Argento et al.	
6,413,276	B1	7/2002	Werblin	9,681,946	B2	6/2017	Kahook et al.	
6,423,094	B1	7/2002	Sarfarazi	9,757,227	B2	9/2017	Kushlin et al.	
6,461,384	B1	10/2002	Hoffmann et al.	9,763,776	B2	9/2017	Lee	
6,464,725	B2	10/2002	Skotton	10,028,824	B2	7/2018	Kahook et al.	
6,488,708	B2	12/2002	Sarfarazi	10,052,196	B2	8/2018	Pugh et al.	
6,537,281	B1	3/2003	Portney	10,080,648	B2	9/2018	Kahook et al.	
6,551,354	B1	4/2003	Ghazizadeh et al.	10,195,018	B2	2/2019	Salahieh et al.	
6,554,859	B1	4/2003	Lang et al.	10,350,056	B2	7/2019	Argento et al.	
6,558,420	B2	5/2003	Green	10,444,541	B2	10/2019	Hyde et al.	
6,596,026	B1	7/2003	Gross et al.	10,485,654	B2	11/2019	Brady et al.	
6,599,317	B1	7/2003	Weinschenk, III et al.	10,526,353	B2	1/2020	Silvestrini	
6,616,691	B1	9/2003	Tran	10,548,718	B2	2/2020	Salahieh et al.	
6,616,692	B1	9/2003	Glick et al.	10,647,831	B2	5/2020	Silvestrini et al.	
6,638,304	B2	10/2003	Azar	10,772,721	B2	9/2020	Rao et al.	
6,695,881	B2	2/2004	Peng et al.	10,799,340	B2	10/2020	Collins et al.	
6,764,511	B2	7/2004	Zadno-Azizi et al.	10,820,985	B2	11/2020	Wortz	
6,767,363	B1	7/2004	Bandhauer et al.	10,842,615	B2	11/2020	Wortz et al.	
6,797,004	B1	9/2004	Brady et al.	10,842,616	B2	11/2020	Silvestrini et al.	
6,818,017	B1	11/2004	Shu	10,856,969	B2	12/2020	Ishikawa	
6,849,091	B1	2/2005	Cumming	11,076,948	B2	8/2021	Kahook et al.	
6,960,231	B2	11/2005	Tran	2002/0128710	A1*	9/2002	Eggleston A61F 2/1613 623/6.22	
6,972,032	B2	12/2005	Aharoni et al.	2003/0088253	A1	5/2003	Seil	
6,991,651	B2	1/2006	Portney	2003/0144733	A1	7/2003	Brady et al.	
7,008,447	B2	3/2006	Koziol	2003/0158560	A1	8/2003	Portney	
7,018,409	B2	3/2006	Glick et al.	2004/0010310	A1	1/2004	Peyman	
7,081,134	B2	7/2006	Cukrowski	2004/0106993	A1	6/2004	Portney	
7,097,660	B2	8/2006	Portney	2004/0117011	A1*	6/2004	Aharoni A61N 1/36046 623/4.1	
7,101,397	B2	9/2006	Aharoni	2004/0148022	A1	7/2004	Eggleston	
7,122,053	B2	10/2006	Esch	2004/0236422	A1	11/2004	Zhang et al.	
7,125,422	B2	10/2006	Woods et al.	2004/0243142	A1	12/2004	Siepsner	
7,150,760	B2	12/2006	Zhang	2005/0015144	A1	1/2005	Tran	
7,186,266	B2	3/2007	Peyman	2005/0027354	A1	2/2005	Brady et al.	
7,198,640	B2	4/2007	Nguyen	2005/0125058	A1	6/2005	Cumming et al.	
				2005/0131535	A1	6/2005	Woods	
				2005/0187621	A1	8/2005	Brady	

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0111776 A1 5/2006 Glick et al.
 2006/0286147 A1 12/2006 Salamone et al.
 2007/0123981 A1 5/2007 Tassignon
 2007/0129801 A1 6/2007 Cumming
 2007/0260308 A1 11/2007 Tran
 2008/0046077 A1 2/2008 Cumming
 2008/0103592 A1 5/2008 Maloney
 2009/0005864 A1 1/2009 Eggleston
 2009/0125106 A1 5/2009 Weinschenk, III et al.
 2010/0016964 A1 1/2010 Werblin
 2010/0047355 A1* 2/2010 Bulte A61K 49/0002
 424/490
 2010/0204787 A1 8/2010 Van Noy
 2010/0298933 A1 11/2010 Knox et al.
 2011/0040378 A1 2/2011 Werblin
 2011/0054600 A1 3/2011 Bumbalough
 2011/0104052 A1* 5/2011 Barnett A61K 9/1635
 424/1.25
 2011/0251686 A1 10/2011 Masket
 2011/0307058 A1 12/2011 Beer
 2011/0313521 A1 12/2011 Angelopoulos
 2012/0078364 A1 3/2012 Stenger
 2012/0179249 A1 7/2012 Coleman
 2013/0184815 A1 7/2013 Roholt
 2013/0190868 A1 7/2013 Kahook et al.
 2013/0296694 A1 11/2013 Ehlers et al.
 2014/0081178 A1 3/2014 Pletcher et al.
 2014/0085599 A1 3/2014 Etzkorn
 2014/0085600 A1 3/2014 Pletcher et al.
 2014/0085602 A1 3/2014 Ho et al.
 2014/0087452 A1 3/2014 Liu et al.
 2014/0088381 A1 3/2014 Etzkorn et al.
 2014/0098226 A1 4/2014 Pletcher et al.
 2014/0107777 A1 4/2014 Portney
 2014/0180411 A1 6/2014 Tornambe et al.
 2014/0192311 A1 7/2014 Pletcher et al.
 2014/0194710 A1 7/2014 Ho et al.
 2014/0194713 A1 7/2014 Liu
 2014/0194773 A1 7/2014 Pletcher et al.
 2014/0371852 A1 12/2014 Aharoni et al.
 2015/0230981 A1 8/2015 Kahook et al.
 2015/0366660 A1* 12/2015 Fernández Martínez
 A61F 2/16015
 623/6.22
 2016/0074154 A1 3/2016 Woods
 2016/0235524 A1 8/2016 Wortz et al.
 2016/0361156 A1 12/2016 Brown
 2017/0319332 A1 11/2017 Kahook et al.
 2017/0348095 A1 12/2017 Wortz et al.
 2018/0161153 A1 6/2018 Kahook et al.
 2018/0263761 A1* 9/2018 Bozukova A61F 2/1654
 2018/0368974 A1* 12/2018 Kahook A61F 2/1662
 2019/0021848 A1 1/2019 Kahook et al.

2019/0321219 A1 10/2019 Ostermeier et al.
 2020/0022840 A1* 1/2020 Kahook A61F 2/1613
 2021/0161655 A1 6/2021 Kaschke et al.

FOREIGN PATENT DOCUMENTS

CA 2350795 C 7/2006
 CA 2407432 C 1/2007
 CA 2480772 C 11/2008
 CA 2959354 C 8/2018
 CA 3095098 A1 10/2019
 CN 104936553 B 3/2017
 CN 107205812 B 11/2019
 CN 107961101 B 12/2019
 DE 102016221371 A1 5/2018
 DE 102017112085 A1 12/2018
 EP 1138282 A1 10/2001
 EP 1202684 B1 4/2003
 EP 1457170 A1 9/2004
 EP 1200019 B1 9/2005
 EP 2042124 A1 4/2009
 EP 1278483 B1 8/2011
 ES 2233049 T3 6/2005
 ES 2300278 T3 6/2008
 ES 2379781 T3 5/2012
 JP S6222641 A 1/1987
 JP S6389154 A 4/1988
 JP H06165793 A 6/1994
 JP 2003524503 A 8/2003
 JP 4261488 B2 4/2009
 JP 4486122 B2 6/2010
 JP 4511533 B2 7/2010
 JP 2012040326 A 3/2012
 JP 5379152 B2 12/2013
 JP 5705529 B2 4/2015
 JP 6030089 B2 11/2016
 JP 6270739 B2 1/2018
 JP 6499307 B2 4/2019
 JP 2019520886 A 7/2019
 JP 6779262 B2 11/2020
 KR 100913267 B1 8/2009
 WO 94/28825 A1 12/1994
 WO 2005084587 A3 9/2005
 WO 2006050171 A2 5/2006
 WO 2008094518 A1 8/2008
 WO 2009073193 A2 6/2009
 WO 2010002215 A2 1/2010
 WO 2012023133 A1 2/2012
 WO 2013112589 A1 8/2013
 WO 2013158942 A1 10/2013
 WO 2014197170 A1 12/2014
 WO 2014204575 A1 12/2014
 WO 2015195825 A1 12/2015
 WO 2016022995 A2 2/2016
 WO 2016126285 A1 8/2016

* cited by examiner




Figure 1A




Figure 1B




Figure 2A




Figure 2B




Figure 2C




Figure 2D




Figure 2E




Figure 3A




Figure 3B




Figure 4




Figure 5




Figure 6A




Figure 6B




Figure 6C




Figure 6D




Figure 7B




Figure 7A




Figure 8




Figure 9B




Figure 9A




Figure 10




Figure 11A




Figure 11B




Figure 11C




Figure 11D




Figure 12A




Figure 12B




Figure 12C




Figure 12D




Figure 13A




Figure 13B




Figure 14A




Figure 14B




Figure 14C




Figure 15A




Figure 15B




Figure 15C

EXCHANGEABLE OPTICS AND THERAPEUTICS

BACKGROUND

An intraocular lens (IOL) is a lens that is implanted in the eye. IOLs come in phakic, designed to be implanted without performing cataract surgery, and pseudophakic, designed to be implanted in conjunction with cataract surgery, varieties. A phakic IOL has the ability to reside in the sulcus space between the capsular bag and the iris or alternatively can reside in the anterior chamber, between the iris and cornea. The most commonly employed pseudophakic IOL is posterior chamber IOL includes haptics that enable the lens to be held in place in the capsular bag inside the eye. Implantation of an IOL is often carried out by an eye surgeon in a surgical center, but may be also be performed at an ophthalmologist's office in an in office surgical suite. In office procedures are particularly common with phakic IOLs, much in the same way laser refractive surgeries are typically in office. The field of pseudophakic IOLs is increasingly addressing the issue of presbyopia, which is the case where someone is not able to see both at distance and near. Presbyopia is not an indication for insurance coverage of cataract surgery currently.

As the field matures, it is likely IOLs will be increasingly utilized to address presbyopia, instead of glare and blurred vision even with glasses or some form of wearable refractive correction which is the current indication. To achieve the quality of vision of laser refractive surgery and to enable incremental changes to the lens as the technology improves, a means of fully customizable and upgradeable IOL design is sorely needed. Refractive cataract surgery replaces the natural eye lens with an advanced multi-focal or extended-depth-of-focus (EDOF) IOL. Refractive cataract surgery has not achieved the precision of corneal refractive surgery, such as LASIK (laser-assisted in situ keratomileusis), which can be individualized to high precision. Moreover, there currently is a lack of wave-front guided precision in cataract extraction and IOL implantation.

A wavefront-guided approach refers to an ablation profile that considers preoperative higher-order aberrations, where the final goal is to avoid inducing aberrations and to eliminate some that exist. This is commonly employed with laser refractive surgery such as LASIK and PRK, as all variables in the eye are known. The laser ablation profile is computed preoperatively according to the results of aberrometry and is transferred to a laser system for use, for example, during surgery. The only modification made to the eye is to the shape of the cornea. Currently this is an elusive task in cataract surgery for two reasons. Principally, the effective lens position, where the IOL ends up in the eye, is hard to determine. Small changes in the anterior posterior position make large changes in the total power of the lens. In addition, zonular weakness induced by the surgery and change in corneal astigmatism made by the cataract main incision can respectively change the lens position and the corneal curvature. Moreover, any customized, astigmatism and higher order aberration correction is precluded a priori on the IOL is precluded by potential shifting of the IOL within the capsular bag in the X, Y, Z plane.

Outside of the inability to provide wavefront guided IOL optimization, current IOL systems do not enable ease of correction if a non-optimal IOL is placed, nor do they allow for ease of upgradeability. IOL exchange is a challenging procedure that even in the most skilled surgeon's hands results in significant trauma to the ocular structures. So

much so that IOL exchange is viewed as a last resort. However, repeated removal and replacement of a conventional IOL may not be an easy procedure and can result in complications. For example, IOL exchange with the conventional IOLs requires dissection of the capsular bag and retrieval of an unfolded lens through the cornea or sclera. Either retrieval approach (through the cornea or through the sclera) is highly traumatic to the eye and its delicate structures. Instead of exchanging IOLs, most surgeons will perform LASIK or other laser refractive procedure to the cornea. This also is not infinitely repeatable as corneal tissue is ablated at each procedure. Repeated laser correction can lead to a host of complications including corneal ectasia and epithelial ingrowth. It also can induce ocular surface disease in even young patients and thus is less than ideal in many of the older individuals undergoing cataract surgery.

A need exists for a system that enables relatively unlimited exchangeable optics as well as wavefront guided lens optimization.

BRIEF SUMMARY

Exchangeable optics and therapeutics are described that can enable progressive application and exchanges of lenses and/or therapeutics in the eye.

An exchangeable optics system includes an intraocular base that can be fixed within an eye. The intraocular base includes one or more couplers and a supporting structure. The one or more couplers can include magnetic material or other releasable fixation material or structures. For example, the releasable couplers can be in the form of a hook and loop coupler, a memory material fixation element such as what is utilized for tagging guns for affixing tags to clothing, a button fastener, a screw-type fastener, a hinge-based fastener similar to a cuff link, a suction cup based mechanism, an adhesive, or any other means of reversible fixation.

Magnetic fixation is particularly attractive as the base element to which the secondary optic couples can be in the capsular bag and the magnetic secondary optic can couple through magnetic force through the anterior capsular bag without physically directly contacting the IOL in the bag. Magnetic attraction is also an ideal mechanism as it allows for a secondary optic to be disengaged from the primary optic with minimal force. Accordingly for magnetic and other types of releasable couplers, it can be important to consider damage to delicate zonules that hold the capsular bag. The supporting structure can include haptics and a main structure that physically supports an exchangeable optic or therapeutic that is coupled via the one or more couplers. In some cases, the intraocular base can include a fixed lens within or on the main structure.

This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A and 1B illustrate exchangeable optics systems suitable for an implantable intraocular lens and application of therapeutics.

FIGS. 2A-2E illustrate various locations in the eye where an exchangeable optics system can be set.

FIGS. 3A and 3B illustrate a perspective view and a top view, respectively, of an exchangeable optic with clips for coupling to an intraocular base.

FIG. 4 illustrates a perspective view of an exchangeable optic with a screw mount for coupling to an intraocular base.

FIG. 5 illustrates a side view of part of an exchangeable optic system with a post and clip coupling.

FIGS. 6A-6D illustrate an exchangeable optics system with multiple stacked lenses.

FIGS. 7A and 7B illustrate another exchangeable optics system with multiple stacked lenses; FIG. 7A shows another example of an intraocular base; and FIG. 7B shows application of a second optic onto the intraocular base and first optic using a delivery system.

FIG. 8 illustrates an optic delivery system consisting of a hook that can be drawn coaxially within a delivery sleeve.

FIGS. 9A and 9B show fiducial designs that can enable precise orientation of three-dimensional rotation of an optic or haptic.

FIG. 10 illustrates an example exchangeable optics system with magnetic exchangeable intraocular lens.

FIGS. 11A-11D illustrate another example of an exchangeable optics system with magnetic exchangeable ocular lens.

FIGS. 12A-12D illustrate example haptic designs for exchangeable optics systems.

FIGS. 13A and 13B illustrate a side view and top view, respectively, of an exchangeable optic with rotatable lens.

FIGS. 14A-14C illustrate an example of an exchangeable optics system with therapeutic delivery.

FIGS. 15A-15C illustrate example magnetic liposomes or nanoparticles that can be used for delivery of therapeutics on an exchangeable optics system.

DETAILED DESCRIPTION

Exchangeable optics and therapeutics are described that can enable progressive application and exchanges of lenses and/or therapeutics in the eye.

FIGS. 1A and 1B illustrate exchangeable optics systems suitable for an implantable intraocular lens and application of therapeutics. As shown in FIGS. 1A and 1B, Exchangeable optics systems include an intraocular base **100** that can be fixed within an eye. The intraocular base **100** includes one or more couplers (e.g., coupler **110**) and a supporting structure **120**. The one or more couplers can include magnetic material or other releasable fixation material or structures. In this example, a single ring-shaped coupler **110** is shown.

Referring to FIG. 1A, an exchangeable optics system **130** can include an intraocular base **100** that supports an exchangeable optic (e.g., **140-A**, **140-B**) and can be fixed within the eye. As mentioned above, the intraocular base **100** can include one or more couplers (e.g., coupler **110**) and a supporting structure **120**. The one or more couplers, in this case, ring-shaped coupler **110**, are used to releasably couple the intraocular base **100** to the exchangeable optic **140-A**, **140-B**. The supporting structure **120** can include haptics **150** for suturing or otherwise fixing the intraocular base **100** in the eye and a main structure **160** (which may be a circular substructure), which can be used to physically support an exchangeable optic **140-A**, **140-B** directly or indirectly via the one or more couplers.

The haptics **150** can be any suitable structure enabling the intraocular base **100** to be fixed within the eye. Various examples are shown in FIGS. 6A, 7A, 10, 11A, and 12A-12D.

In the illustrated scenario, the main structure **160** is open in the center such that the exchangeable optic **140-A**, **140-B** rests on a proximal surface at the perimeter of the intraocular base **100**. In other implementations, the main structure **160** has a transparent surface over which the exchangeable optic **140-A**, **140-B** rests. The supporting structure **120** can also optionally include a lens or IOL (not shown) within or on the main structure **160**. In some cases, the supporting structure **120** can include one or more protrusions that can be used to extend up through a hole in the capsular bag of the eye (see e.g., extensions **222** of FIG. 2B and tension ring extensions **1125** of FIG. 11A). In some of such cases, a coupler can be disposed at an end of a protrusion. This coupler may be the coupler for the base or an additional coupler for the base.

The exchangeable optic **140-A**, **140-B** can include a lens **170** and one or more corresponding couplers **180**. For application of the exchangeable optics system **130**, the intraocular base **100** can be deployed in an eye. One of the exchangeable optics **140-A**, **140-B** can then be deployed, oriented/aligned, and coupled to the intraocular base **100** using the couplers **110**, **180** (illustrated as magnets/magnetic material). Alignment can involve radial alignment with respect to either the intraocular base, the eye, or some structure within the eye. The one or more exchangeable optics (e.g., optic **140-A**, **140-B**) can include fiducials to aid in radial alignment, such as seen in FIGS. 9A and 9B. Alignment can also involve depth alignment with respect to either the intraocular base, the eye, or some structure within the eye.

In some cases, there are more or fewer “corresponding couplers” **180** than there are couplers **110** of the intraocular base **100**. For example, the couplers of the base may be point couplers while the couplers of the optic may be a single ring shape. In the illustrated scenario, one exchangeable optic **140-A** is shown with a single corresponding coupler **180**, which is in the shape of a ring; and the other exchangeable optic **140-B** is shown with two corresponding couplers **180** that are positioned to both couple to the ring-shaped coupler **110** of the intraocular base **100**. The coupling between the intraocular base **100** and the exchangeable optic **140-A**, **140-B** can be accomplished in a variety of ways, for example, magnetically, using friction, or chemically. In the illustrated scenario, magnetic coupling is shown.

Of course, while a ring-shape coupler **110** is one example, the one or more couplers at the intraocular base may be two couplers formed of magnetic material such that the coupling is accomplished using a two-point coupling where a first of the one or more couplers of the intraocular base is disposed at a proximal surface (i.e., the surface facing outward from the eye) on one side of the intraocular base and a second of the one or more couplers is disposed at the proximal surface on another side of the intraocular base. The corresponding one or more couplers would then be disposed at the exchangeable optic in a manner to orient and couple the exchangeable optic to the base. For example, the corresponding one or more couplers would be disposed in alignment for coupling to the one or more couplers of the intraocular base.

As mentioned above, the one or more couplers **110** and the corresponding one or more couplers **180** can be formed of magnetic material. The magnetic material can be any suitable ferromagnetic or ferrimagnetic material. The magnetic material is sized and shaped so as to minimize or avoid susceptibility to strong external magnetic fields such as MM (e.g., avoiding/minimizing movement or interference with imaging).

It should be understood that although the examples contained herein make reference to the couplers being magnets or magnetic, other types of releasable couplers can be used (e.g., chemical, mechanical, or friction based) in certain implementations. The use of magnetic couplers also enable certain therapeutics to be applied.

Indeed, referring to FIG. 1B, the same intraocular base **100** can be used to apply therapeutics **190**. In the illustrated scenario, therapeutics **190** can be coupled to the intraocular base **100**. In some cases, the therapeutics **190** are applied once the intraocular base **100** is deployed in the eye. In some cases, the therapeutics **190** may be applied before original deployment and then optionally reapplied after deployment.

FIGS. 2A-2E illustrate various locations in the eye where an exchangeable optics system can be set. FIGS. 2A-2C show examples of an intraocular base of an exchangeable optics system being positioned within a capsular bag of the eye. Referring to FIG. 2A, an intraocular base **200** of an exchangeable optics system **210** can be positioned within the capsular bag **212** of an eye. Through use of magnetic coupling, an exchangeable optic **215** (or therapeutic) can be deployed to (and even later removed from) the sulcus space **216** of the eye. Referring to FIG. 2B, an intraocular base **220** having extensions **222** can be positioned within the capsular bag **212** of an eye. The extensions **222** (or other protruding structure) can be extended into the sulcus space **216** through one or more holes in the capsular bag **212**. For example, there may be an opening from cataract surgery through which the extensions **222** can protrude. In some cases, small openings may be made to allow for the extensions **222** to protrude through. Magnetic, mechanical, or chemical couplers may be provided at the end of the extensions **222** for an exchangeable optic **225** that is deployed to (and even later removed from) the sulcus space **216** to couple to. Referring to FIG. 2C, an exchangeable optics system **230** can be positioned entirely within the capsular bag **212**.

Referring to FIG. 2D, in some cases, an exchangeable optics system **240** can be positioned entirely in the sulcus **216** behind the iris **242**, in front of the capsular bag **212**. Referring to FIG. 2E, in some cases, an exchangeable optics system **250** can be positioned in the anterior chamber behind the cornea **252**, in front of the iris **242**. The examples shown in FIGS. 2D and 2E could work with a patient that is phakic (with native lens). Advantageously, if the intraocular base is fixed in the anterior chamber (such as shown in FIG. 2E) or in the sulcus space (such as shown in FIG. 2D), cataract surgery may not be required.

For any of these locations, if weight of the system is ever greater than zonular strength, an air bladder or portion of the device that floats in aqueous can be incorporated in the intraocular base. This buoyant component of the invention can be permanently incorporated, for example a compressible foam buoy that has sealed foam used in nautical equipment, pool toys and body boards. Alternatively, the device can have a reservoir that acts as a bladder that is filled with a gas or any material lighter than water. This would enable adjustable buoyancy based upon the degree of fill.

As mentioned above, the one or more couplers **110** (and corresponding one or more couplers **180**) can include magnetic material or other releasable fixation material or structures. For example, the releasable couplers can be in the form of a hook and loop coupler, a memory material fixation element such as what is utilized for tagging guns for affixing tags to clothing, a button fastener, a screw-type fastener, a hinge-based fastener similar to a cuff link, a suction cup based mechanism, an adhesive, or any other means of reversible fixation.

FIGS. 3A and 3B illustrate a perspective view and a top view, respectively, of an exchangeable optic with clips for coupling to an intraocular base; FIG. 4 illustrates a perspective view of an exchangeable optic with a screw mount for coupling to an intraocular base; and FIG. 5 illustrates a side view of part of an exchangeable optic system with a post and clip coupling.

Referring to FIGS. 3A and 3B, an exchangeable optic **300** can have a clip **310** that can attach to a coupler of an intraocular base (not shown). In some cases, the exchangeable optic **300** can include ribs **320** to assist with a secure fit, for example, within a main structure of the intraocular base.

Referring to FIG. 4, an exchangeable optic **400** can have a screw mount **410** for securing to a corresponding coupler at an intraocular base (not shown). In some cases, the exchangeable optic **400** can include prongs **420** to assist with a secure fit, for example, within a coupler and main structure of the intraocular base.

Referring to FIG. 5, an exchangeable optic **510** can be coupled to an intraocular base **520** using a post **530** and nitinol clip **540**.

For any direct connection between a base and an exchangeable optic (or between two exchangeable optics), it is desirable that the coupling mechanism is located within the confines of the anterior rhexis. This will enable direct connection between the exchangeable optic (e.g., exchangeable optic **225** of FIG. 2B) outside of the capsular bag **212** and the intraocular base (e.g., intraocular base **220** of FIG. 2B) in the capsular bag. Alternatively, femtosecond laser or other precision surgical platform can not only make the primary rhexis but also make two or more small secondary opening in the anterior capsule through which a coupling mechanism (e.g., extensions **222**) can protrude. The use of the femtosecond laser or other precision surgical platform to form secondary openings through which a coupling mechanism can protrude may serve a secondary function of aligning a lens in a particular axis, which is useful, for example, with toric IOLs. Indeed, the femtosecond laser or other precision surgical platform can be used to make two additional holes adjacent to the rhexis at the axis the IOL must be through.

There are numerous coupling mechanisms that may be used instead of or in addition to magnetic material. In some cases, the exchangeable optic can have a fixation element that has a shape memory material component that can be placed through a hole at the intraocular base through the holes made in the anterior capsule. Similar to a tagging gun used to attach price tags to clothing, the T arms can flex when being pushed through the hole in the optic haptic junction and return to an open position once through the hole.

As is clear to one skilled in the art, this arrangement can be modified in numerous ways. For example, in some cases, the T arm fixation element can be incorporated into the intraocular base and project through the capsular bag into the sulcus space. The exchangeable optic can have a hole in it through which the T fixation element projects. This may be a preferable option if capsular bag phimosis causes the capsular bag to shift in position in relation to the hole in the primary optic. By having the T fixation element project beyond the capsular bag, this helps ensure maintained access to the coupling mechanism, even if capsular phimosis occurs. In addition, the T-shape fixation element can be made of a variety of memory materials including shape memory polymers and shape memory metals. Suitable memory polymers for the described fixation elements include, but are not limited to, polynorbomene, polycaprop-

lactone, polyenes, nylons, polycyclooctene (PCO), blends of PCO and styrene-butadiene rubber, polyvinyl acetate/polyvinylidene fluoride (PVAc/PVDF), blends of PVAc/PVDF/poly methylmethacrylate (PMMA), polyurethanes, styrene-butadiene copolymers, polyethylene, trans-isoprene, blends of polycaprolactone and n-butylacrylate, and combinations thereof. Suitable memory metals for the described fixation elements include, but are not limited to, stainless steel, cobalt, nickel, chromium, molybdenum titanium, nitinol, tantalum, platinum-iridium alloy, gold, magnesium, or combinations thereof. Further, it should be understood that other end shapes may be used for the T shape fixation element. For example, the end shape may be a circle, triangle or any shape that is larger than the hole it is to be fixated through.

In some cases, the intraocular base or the exchangeable optic can have posts that project either through the anterior capsulotomy or through the secondary holes created in the anterior capsule. In one such implementation with a post projection, an exchangeable optic could then fit through the posts and an elastic band can be placed over the exchangeable optic onto the post thereby holding the exchangeable optic in place. The elastic band that retains the exchangeable optic can operate similar to how rubber bands hold a wire in place to the bracket on dental braces. In another implementation of a post projection, the post could have a thread on it in which a screw can mount. In another implementation, the post can include a hole through which a cotter pin or memory material can be placed through. In another implementation, the post can include a lever arm. Similar to a cuff link, the post can either be straight up and down or when turned at the hinge will form a T. This arrangement does not involve shape memory but instead just a mechanical hinge. An exchangeable optic with a feature similar to a shirt cuff can be threaded over the fixation element when it is in a straight position and then once in place the hinge can be turned so instead of straight the post forms a T thereby holding the exchangeable optic and the intraocular base together.

In some cases, the intraocular base and the exchangeable optic can use a snap-button arrangement, for example, if designed with low enough friction.

In some cases, the intraocular base and the exchangeable optic can use a twist on mechanism in conjunction with posts, where the posts include a T or L shaped end and once the posts pass through the opening in the other part, the exchangeable optic can be rotated so that the end of each post catches on a surface to hold the two in place. For example, if one post element is in the shape of a L but the slot it passes through only is slightly larger than the horizontal component of the L, then if the intraocular base and the exchangeable optic are rotated in relation to each other, the leading edge of the L moves beyond the edge of the slot it passes through thereby holding the intraocular base and the exchangeable optic together. In some cases, a shape memory material can be incorporated. For example, the L shape can have a projection at the very end (such as in the form of a very pronounced serif L). The projection at the end of the L can fit into a hole that is adjacent to the notch (e.g., similar to that employed in some ballpoint pens). Thus, as the L shape is threaded through the notch, the projection portion at the end of the L abuts the edge of the notch and is bent slightly out of the way so rotation can continue. Once rotated far enough that the projection on the L reaches the hole next to the notch and falls into place thereby enabling the L to again be coplanar with the intraocular base and

exchangeable optic. In some cases, both the exchangeable optic and the L shaped post can be formed of materials with memory shape properties

FIGS. 6A-6D illustrate an exchangeable optics system with multiple stacked lenses. FIG. 6A illustrates an exploded view of an exchangeable optics system **600** that includes an intraocular base **610** and a plurality of optics (including first optic **621** and second optic **622**). The intraocular base **610** can have a supporting structure **630** with a haptic ring **640** that can be sutured for fixed connection to an eye. One or more couplers can be on the supporting structure. For example, the one or more couplers can be point sources or a ring (such as represented by white dotted line **650**) that is disposed on or goes around a circumference of the supporting structure (see also e.g., FIGS. **11A** and **11B**). Referring to FIG. 6B, the intraocular base **610** can be disposed in the eye (e.g., in the sulcus space). As shown in FIG. 6C, the first optic **621** can be releasably attached to the intraocular base **610**. Alternatively, in some cases, the first optic **621** (or a third optic) is fixedly attached to the intraocular base **610** or is built-in to the intraocular base (see e.g., lens **1060** of FIG. **10**). Then, as shown in FIG. 6D, the second optic **622** can be releasably attached to the intraocular base **610** over the first optic **621**. In some cases, the magnetic force from the intraocular base **610** is sufficient to couple both optics. In some cases, the positioning of the two optics enable at least a portion of the one or more couplers to be dedicated to a respective one of the two (or more) optics. In some cases, the first optic **621** includes one or more couplers for the second optic **622** to couple to. In some cases, the first optic **621** is fixedly attached to the intraocular base **610** and the couplers on the supporting structure are configured for attachment of the second optic **622**.

FIGS. 7A and 7B illustrate another exchangeable optics system with multiple stacked lenses; FIG. 7A shows another example of an intraocular base; and FIG. 7B shows application of a second optic onto the intraocular base and first optic using a delivery system.

Referring to FIG. 7A, an intraocular base **710** can have a supporting structure **720** with a haptic **730** that can be sutured for fixed connection to an eye. One or more couplers can be on the supporting structure **720**. For example, the one or more couplers can be point sources or a ring (such as represented by white dotted line **740**) that is disposed on or goes around a circumference of the supporting structure (see also e.g., FIGS. **11A** and **11B**).

Turning to FIG. 7B, a lens **750** can be easily applied to the intraocular base **710** via a tool (optic delivery system **760**) through a small incision in the sclera **770**. An optic delivery system **760** can include a hook or other fine instrument that can be drawn coaxially, allowing for a minimal incision that minimizes changes to corneal astigmatism and damage to the ocular structures after optic introduction or exchange. The optic delivery system can coaxially store a capsular bag containing a new optic containing, for example, the secondary lens **750** and enter through a minimal incision. As shown in FIG. 7B, once inside the eye close to the location of the intraocular base **710**, the optic delivery system **760** can release the capsular bag close into the sulcus space. The hook (see FIG. **8**) can be used to maneuver the capsular bag or secondary lens to be oriented properly with respect to the intraocular base **710**. At some point, the new optic **750** can couple to the intraocular base, at which point the hook can optionally be used to properly orient the new optic with respect to the intraocular base. Fiducial markers may be used to facilitate orientation and alignment (see e.g., FIGS. **9A** and **9B**, which can be used under optical coherence tomog-

raphy—OCT) In some cases, the exchangeable optics (e.g., lens **750**) can include an aperture, which may be hooked by the instrument of the optic delivery system.

In this illustrated scenario, the lens **750** is a second optic; however, this method can be carried out for the first optic (e.g., optic **621**) and even a replacement second optic (e.g., to replace the second optic **622** after optic **622** is applied as shown in FIG. **6D**).

FIG. **8** illustrates operation of an optic delivery system. Referring to FIG. **8**, an optic delivery system **810** can include a hook **815**, which can be drawn coaxially into the eye within a delivery sleeve of the optic delivery system **810**. In a first step, the hook **815** can be in the extended position. As illustrated in a second step, the hook **815** can engage a hole **825** within the periphery of the optic **820** to enable extraction. As illustrated in the third step, the hook **815** can then be drawn coaxially back into the optic delivery system **810**, bringing the optic **820** towards the delivery sleeve. At a certain point, the hook **815** can be drawn entirely within the optic delivery system **810**, at which point the optic **820** can be forced to fold inwards and be drawn with the hook into the optic delivery system **810**, such as shown in step **4**.

FIGS. **9A** and **9B** show fiducial designs that can enable precise orientation of three-dimensional rotation of an optic or haptic. Fiducials can be placed, etched, or drawn onto a lens or other optic to aid in orientation of the lens or other optic once deployed. The fiducial markers can be of a material suitable for detection by IR, ultrasound, fluorescent, x-ray, MRI, etc. In one implementation, the fiducials can be detectable by an ocular response analyzer (e.g., optical coherence tomography—OCT). The fiducial markers can be used to determine precise effective lens position (ELP). Corresponding markers can be applied to an intraocular base at haptics, on the optional lens, or on the supporting structure, as some examples. In some cases, a corresponding fiducial design may be disposed at the intraocular base (e.g., on main structure region **160** of FIG. **1A**).

Referring to FIG. **9A**, the fiducial can be L-shaped. Arms of the L shape can vary. If the size and shape of the L-shaped fiducial is known, apparent length can be used to inform rotation of the lens or optic in three dimensions. Referring to FIG. **9B**, the fiducial can be bulls-eye-shaped (e.g., a single dot within a circle). In particular, use of a bulls-eye shape can allow part of the fiducial to be printed on an opposite side of the lens or optic. The fiducial being on both sides of the lens or optic can create greater apparent motion of the dot relative to the circle, allowing a more accurate understanding of its orientation in three-dimensional space.

A few L shaped fiducials printed on one side of the lens or haptic receiving system (e.g., as shown in FIG. **9A**) or a circle on one side of the lens and a dot on the other placed within the circle when viewed anterior/posterior (e.g., providing a bullseye such as shown in FIG. **9B**) will enable a sensitive measurement of any tilt. By visualizing the length of the L arms or where the dot is in relation to the circle it is possible to determine where the lens or haptic receiver is located.

In some implementations, fiducials are provided on both the exchangeable optic and the intraocular base that can be read using OCT. The fiducials can be read in relation to a stationary feature of the eye (e.g., conjunctival vessel pattern preregistered with corneal topography/tomography, biometry data, etc.). The OCT can then guide placement of the optic on haptic. The fiducials support real time tracking of the intraocular base in case the intraocular base moves when the exchangeable optic is removed. When the exchangeable

optic is repositioned or replaced, the OCT device can calculate in real time with the fiducials what position change is necessary.

As mentioned above, an exchangeable optics system can include a variety of structures for the intraocular base. In addition, the couplers of the intraocular base can be disposed in various locations and be configured in various shapes. The following examples are directed to exchangeable optics systems with intraocular bases having magnetic coupling; however, embodiments are not limited thereto.

FIG. **10** illustrates an example exchangeable optics system with magnetic exchangeable intraocular lens. Referring to FIG. **10**, an exchangeable optics system **1000** can include an intraocular base **1010** with haptics **1020** and a circular magnet coupler **1030**; and an exchangeable optic **1040**. The exchangeable optic **1040** can be a magnetic optic with a corresponding circular magnet **1050** around its periphery.

In the illustrated scenario, the haptics **1020** are in the form of a two C-loop haptic. In some cases, the intraocular base **1010** can further include a lens **1060**. For example, the intraocular base **1010** can be similar to a conventional IOL, but further includes the one or more couplers (e.g., here in the form of a magnet disposed at a periphery). A magnetic optic **1040** can then be deployed, rotated to any precise orientation, for example aligned using fiducials such as shown in FIGS. **9A** and **9B**, and coupled to the intraocular base structure **1010**. In some cases, the exchangeable optic **1040** may not be deployed for potentially years down the line and/or may be replaced years later to deploy a more precise lens. An intraocular base structure **1010** that allows for deployment, rotation, and coupling of a magnetic optic (e.g., exchangeable optic **1040**) can be advantageous, for example, in precise toric astigmatism correction. In addition, since it is possible to add additional lenses and/or replace the exchangeable optic **1040**, it is possible to add a further corrective lens after a more disruptive surgery, add a corrective lens years after the fact, or deploy a more precise lens, for example a specially made or three-dimensional printed lens.

FIGS. **11A-11D** illustrate another example of an exchangeable optics system with magnetic exchangeable ocular lens. Referring to FIGS. **11A** and **11D**, in exchangeable optics system **1100**, an intraocular base **1110** can include a capsular tension ring **1120** with optional tension ring extensions **1125** and two or more couplers **1130**. As mentioned above with respect to FIG. **2B**, through use of one or more protrusions such as tensions ring extensions **1125**, the capsular tension ring **1120** can be designed in such a way that two or more magnetic arms (e.g., tension ring extensions **1125** with couplers **1130**) emerge through the anterior capsulotomy similar to an Ahmed segment thereby enabling optic placement in the sulcus space. Alternatively, the capsular tension ring can be designed such that the capsular tension ring does not rise up out of the anterior capsulotomy but instead remains in bag. In some cases, in addition to the couplers **1130** or as an alternative to the couplers **1130**, a secondary magnet ring **1140** can be included, which can provide a 360-degree docking platform for magnetic optics **1150**, as shown in FIGS. **11C** and **11D**. That is, as shown in FIG. **11C**, an optic with corresponding couplers can be deployed, and attraction between the couplers **1130** on the arms of the capsular tension ring **1120** (and/or optionally the secondary magnet ring **1140**) and the corresponding couplers on the optic **1150** can releasably maintain the optic **1150** in place.

FIGS. **12A-12D** illustrate example haptic designs for exchangeable optics systems. A supporting structure of an

intraocular base can be implemented with haptics of a variety of different shapes and patterns. In addition to the shapes shown in FIGS. 6A and 7A, the two-looped C shaped haptic such as shown in FIG. 10 and the capsular tension ring configuration shown in FIG. 11A, other haptic shapes may be used. For example, FIG. 12A shows an exchangeable optics system 1200 with an intraocular base 1210 design having a cruciate haptic pattern 1215 and a magnetic coupling optic 1220. FIG. 12B shows an exchangeable optics system 1230 with an intraocular base 1240 design having a haptic design 1245 that can facilitate secondary scleral sutured lens similar to the Gore Akreos lens and a magnetic coupling optic 1220. FIG. 12C shows an exchangeable optics system 1250 with an intraocular base 1260 design with four-pronged haptic arm 1265 and a magnetic coupling optic 1220. FIG. 12D shows an exchangeable optics system 1270 with an intraocular base 1280 design with looped haptic 1285 and a magnetic coupling optic 1220.

With cataract surgery, the shape of the corneal as well as the optics of the lens and the effective lens position are altered. Even if precisely positioned in the appropriate location, postoperative shifting of the lens is not uncommon. An exchangeable optics system such as described herein can address these obstacles. First, by sandwiching the capsular bag between the magnetic optic and magnetic haptic receiver through the bag, the system is less likely to rotate or shift in relation to the capsular bag. Second, in certain embodiments, such as 3D printing of a wavefront guided custom intraocular lens, it may make more sense to allow an intraocular base with a lens haptic system to scar into the capsular bag. As the capsule contracts, the final effective lens position of the intraocular base will then be known. By including fiducials, a wavefront scan can calculate shape of cornea after cataract surgery, an effective lens position can be determined from fiducials, and this data can be used to 3D print a custom lens when all variables are achieved. The custom lens can then be attached afterwards to the determined specifications. This would enable the ability to not only print wavefront optimized monofocal IOLs, but also custom wavefront optimized multifocal and extended depth of focus intraocular lens. An intraocular base also provides a forward compatible system for any future iteration of lens since the lens can be replaced/exchanged with the newest iteration of the lens.

In some of such cases, the lens providing the primary power can be deployed with the intraocular base (see e.g., lens 1060 described with respect to FIG. 10) and a wavefront guided optic can be delivered secondarily for attachment to the intraocular base that has the lens 1060. The wavefront guided optic ("second lens") can be deployed through a far smaller incision and similar to ICL surgery and LASIK, may be amenable to office-based procedures. That is, the secondary optic can be deployed through a small enough corneal incision or previous surgical incisions can be accessed, and the additional variability created by reentering cornea can be minimized. This would enable the primary lens and haptic system to be deployed in the bag similar to current IOLs, just with a magnetic system. At a secondary time period in which the capsular bag has fully contracted, the fiducials provide effective lens position. In addition, by using topography/tomography and wavefront measurements of the length of the eye, all the optical variables could be controlled for. If necessary, the degree of astigmatism induced by penetrating the cornea to deliver the secondary optic can be controlled for with custom optic design adjusted to account for the induced astigmatism. Thus, it is possible to a priori deter-

mine effective lens position (ELP) and determine what custom or non-custom lens would be ideal for an eye.

Specialized optics can be applied to an intraocular base as part of the described exchangeable optics systems. FIGS. 13A and 13B illustrate a side view and top view, respectively, of an exchangeable optic with rotatable lens. A lens housing system is provided for a rotational design that enables rotation of a lens of intraocular base or an exchangeable optic. Referring to FIG. 13A, a design for an exchangeable optic 1300 can have a coupling frame 1310 to which couplers 1320 of an intraocular base 1330 can be attached; a stationary body 1340 that can fit within an opening of the intraocular base 1330 and a rotating body 1350 which can rotate in one or two dimensions, depending on coupling between the stationary body 1340 and the rotating body 1350.

As previously mentioned, an intraocular base can be used not just to support delivery of exchangeable optics, but also to provide a surface for delivery of therapeutics. FIGS. 14A-14C an example of an exchangeable optics system with therapeutic delivery.

Magnetic liposomes or nanoparticles can be used in conjunction with magnetic components of an exchangeable optics system.

In addition to incorporating drug delivery polymeric implants or reservoirs directly into the haptic or optic system of the device, the magnetic components of the intraocular base provide a means of coupling magnetic nanoparticles and liposomes to the device. The magnetic liposomes or particles may be preloaded onto the device and administered at the time of surgery or after surgery.

Magnetic liposomes or nanoparticles can be coupled to a magnetic intraocular base prior to deployment in the eye. Alternatively, or in addition, liposomes or nanoparticles can be introduced through an intravitreal, transzonular, intracapsular or intracameral approach after deployment of a magnetic intraocular base into the eye and be coupled to the magnetic intraocular base in the eye. The magnetic particles can be used to deliver therapeutics including, but not limited to antibiotics, steroids, and non-steroidal anti-inflammatory drugs (NSAIDs). These therapeutics can be configured such as illustrated in FIGS. 15A-15C to facilitate attachment to an intraocular base. Instead of rapidly exiting the eye through the normal outflow pathways, a magnetic intraocular base would enable the magnetic particles to dwell on the haptic system until they degraded or release ferrofluid to the point that the magnetic attraction is no longer sufficient to remain bound.

As mentioned above, the magnetic particles used to deliver the therapeutics can be applied to various forms of an intraocular base. Referring to FIG. 14A, an intraocular base 1410 in the form of a capsular tension ring can be formed of or coated with magnetic material that attracts the magnetic particles. In some cases, different regions can be applied with different therapeutics, for example, a region for antibiotics 1412, a region for steroid 1414, and a region for NSAID 1416. Of course, the therapeutics may be applied in a manner that the various therapeutics are disbursed throughout the surface of the intraocular base 1410.

Referring to FIG. 14B, an intraocular base 1420, with or without a lens, can include a magnetic coupler/ring 1422 that is used to attach magnetic particles 1430. The magnetic particles 1430 can thus be deployed and attached around the ring 1422.

Referring to FIG. 14C, an intraocular base 1440 with magnetic haptics 1442 can be used to attach magnetic particles 1450.

13

Referring to FIG. 15A, a magnetic particle can be formed of a magnetite core with polymer coating and polyethylene glycol shell. The magnetite cores can cause the magnetic particle to be attracted to the magnetic intraocular base allowing for relatively fine deployment. If a plurality of magnetite particles is present, attraction between the magnetic particle and the magnetic intraocular base is reduced. The strength of the magnetic on the magnetic intraocular base as well as the concentration of the magnetite, size of polymer particle, and rate of degradation can adjust the dwell time to further finetune localized dosage. In a particular embodiment, rate of polymer degradation can be tuned to drug release rate. This can allow the magnetic particle to disassociate after the majority—or even all of—the drug is delivered due to a decreased attraction.

Referring to FIG. 15B, a magnetic particle can have a plurality of magnetic particles within a single polymer particle instead of a single magnetite core as shown in FIG. 15A.

Referring to FIG. 15C, a magnetic particle can be formed as a liposome particle with a ferrofluid core. A therapeutic can include a liposome shell, a magnetic ferrofluid within the liposome shell, and a drug or therapeutic core within the liposome shell. The magnetic ferrofluid and drug or therapeutic core can be combined inside the liposome shell. Since the ferrofluid and therapeutics are combined within the liposome shell, release of the drug or therapeutic can coincide with release of the ferrofluid. In certain implementations, rate of ferrofluid release can be tuned to drug release rate so when the majority of drug is released the degree of attraction between the liposome and intraocular base is reduced to the point at which the liposome dissociates and then can freely flow through the trabecular meshwork out of the eye.

Since free iron is known to be toxic to the retina, magnetic nanoparticles are contained within a biocompatible shell much like current iron-based MM contrast agents such as Ferridex® from Berlex Laboratories Inc. The nanoparticles are of sufficient size in order for them to freely egress out of the eye through the trabecular meshwork when the extraocular magnet is removed. The nanoparticles are then cleared by the liver like other iron-based nanoparticles currently used clinically.

The biocompatible material for the biocompatible shell of the magnetic nanoparticles can be selected from the group consisting of polyvinyl alcohol, sodium polyacrylate, acrylate polymers, hyaluronase polymers, collagen membrane, Porous HA/TCP ceramic composite, hydroxyapatite bone cement, PVP/PMMA, tricalcium phosphate, hydroxyapatite coated collagen fibers, calcium sulphate, hydroxyapatite (HAp), phosphorylcholine (PC), silicone, ultrahigh molecular weight polyethylene, polyethylene, acrylic, nylon, Polyurethane, Polypropylene, poly(methyl methacrylate), Teflon, Dacron, acetal, polyester, silicone-collagen composite, polyaldehyde, polyvinyl chloride, silicone-acrylate, poly(tetrafluoroethylene), hydroxyethyl methacrylate (HEMA), poly(methyl methacrylate) (PMMA), poly(glycolide lactide), poly(glycolic acid), tetrafluoroethylene, hexafluoropropylene, poly(glycolic acid), poly(lactic acid), desamino-tyrosyltyrosine ethyl ester, polydioxanone, fibrin, gelatin, hyaluronan, tricalcium phosphate, polyglycolide (PGA), polycaprolactone, poly(lactide-co-glycolide), polyhydroxybutyrate, polyhydroxyvalerate, trimethylene carbonate, polyhydrides, polyorthoesters, poly(vinyl alcohol), poly(N-vinyl 2-pyrrolidone), poly(ethylene glycol), poly(hydroxyethylmethacrylate), n-vinyl-2-pyrrolidone, methacrylic acid, methyl methacrylate, and maleic anhydride,

14

polycaprolactone, poly(amino acids), poly(L-lysine), poly(l-ornithine), poly(glutamic acid), polycyanoacrylates, polyphosphazenes, poly(lactic acid), poly(glycolic acid), crown ethers, cyclodextrins, cyclophanes, ethylene glycol, Methylacrylate, Para-xylylene, Biodegradable Copolymers, Copolymer Surface Coatings, Starch Polymers, Poly(lactic acid), Cellophane, Tyrosine Polycarbonates Lactide and Glycolide Polymers, Collagen, PTFE, silicone, Keratin-Based Materials, Fibrous Composites—Carbon Fiber and Particles, Polymer Composites, Artificial/Natural Material Composites, Glass-Ceramic/Metal Composites, Glass-Ceramic/Non-metal Composites, Dental Composites, hydrogels, timed-release foams, and polymeric carriers.

According to certain implementations, the magnetic nanoparticles can include metal oxide and polymeric or liposomal formulations. Example liposomes include elements from the group consisting of fatty acids, fatty acids derivatives, mono-, di and triglycerides, phospholipids, sphingolipids, cholesterol and steroid derivatives, oils, vitamins and terpenes including but not limited to egg yolk L-phosphatidylcholine (EPC), 1,2-dimyristoyl-sn-glycero-3-phosphatidylcholine (DMPC), 1,2-dipalmitoyl-sn-glycero-3-phosphatidylcholine (DPPC), 1,2-dioleoyl-sn-glycero-3-phosphatidylcholine (DOPC), 1,2-distearoyl-sn-glycero-3-phosphatidylcholine (DSPC), 1,2-dilauroyl-sn-glycero-3-phosphatidylcholine (DLPC), 1,2-dioleoyl-sn-glycero-3-phosphoethanolamine (DOPE), 1-palmitoyl-oleoyl-sn-glycero-3-phosphoethanolamine (POPE), 1,2-dimyristoyl-sn-glycero-3-phosphoethanolamine (DMPE), 1,2-dipalmitoyl-sn-glycero-3-phosphoethanolamine (DPPE), and 1,2-distearoyl-sn-glycero-3-phosphoethanolamine (DSPE), phosphatidic acids, phosphatidylcholines with both saturated and unsaturated lipids, phosphatidyl ethanolamines, phosphatidylglycerols, phosphatidylserines, phosphatidylinositols, lysophosphatidyl derivatives, cardiolipin, 13-acyl-y-alkyl phospholipids, di-oleoyl phosphatidylcholine, di-myristoyl phosphatidylcholine, di-pentadecanoyl phosphatidylcholine, di-lauroyl phosphatidylcholine, dipalmitoylphosphatidylcholine, distearoylphosphatidylcholine, diarachidoylphosphatidylcholine, dibehenoylphosphatidylcholine, ditricosanoylphosphatidylcholine, dilignoceroylphosphatidylcholine; and phosphatidylethanolamines.

The polymer formulations (e.g., forming a matrix for the nanoparticles) can be selected from the group consisting of poly(acrylamide), poly(N-isopropylacrylamide), polyisopropylacrylamide-co-1-vinylimidazole, poly(N,N-dimethylacrylamide), poly(N,N-dimethylacrylamide), poly(1-vinylimidazole), poly(sodium acrylate), poly(sodium methacrylate), poly(2-hydroxyethylmethacrylate) (HEMA), poly N-dimethylaminoethyl methacrylate (DMAEMA), poly(N tris(hydroxymethyl)methylacrylamide), poly(1-(3-methacryloxy)propylsulfonic acid) (sodium salt), poly(allylamine), poly(N-acryloxysuccinimide), poly(N-vinylcaprolactam), poly(1-vinyl-2-pyrrolidone), poly(2-acrylamido-2-methyl-1-propanesulfonic acid) (sodium salt), poly((3-acrylamidopropyl) trimethylammonium chloride), and poly(diallyldimethylammonium chloride), poly(hydroxy acids), polyanhydrides, polyorthoesters, polyamides, polycarbonates, polyalkylenes, polyalkylene glycols, polyalkylene oxides, polyalkylene terephthalates, polyvinyl alcohols, polyvinyl ethers, polyvinyl esters, polyvinyl halides, polyvinylpyrrolidone, polysiloxanes, poly(vinyl alcohols), poly(vinyl acetate), polystyrene, polyurethanes and copolymers thereof, synthetic celluloses, polyacrylic acids, poly(butyric acid), poly(valeric acid), and poly(lactide-co-caprolactone), ethylene vinyl acetate, copolymers and blends thereof.

15

Advantageously, the described intraocular base enables customization and exchange of optics as well as delivery of therapeutics.

Although the subject matter has been described in language specific to structural features and/or acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as examples of implementing the claims and other equivalent features and acts are intended to be within the scope of the claims.

What is claimed is:

1. An exchangeable optics system comprising:
an intraocular base comprising:

- one or more couplers for releasably coupling to an exchangeable optic or therapeutic; and
 - a supporting structure for physically supporting the exchangeable optic or therapeutic when coupled to the intraocular base via the one or more couplers, the supporting structure comprising haptics for fixedly coupling the intraocular base within an eye, a main structure, and a first set of fiducials; and
 - a therapeutic releasably coupled to the intraocular base, wherein the supporting structure comprises an intraocular lens (IOL), and wherein the main structure comprises a primary optic of the intraocular lens,
- wherein the one or more couplers are magnetic couplers located on a periphery of the main structure or on the haptics,

16

wherein the therapeutic comprises a magnetic particle, and wherein the magnetic particle comprises:

- a liposome shell;
 - a magnetic ferrofluid within the liposome shell; and
 - a drug or therapeutic core within the liposome shell.
2. The exchangeable optics system of claim 1, further comprising:
- the exchangeable optic, wherein the exchangeable optic comprises one or more corresponding couplers for coupling with one or more magnetic couplers located on a periphery of the main structure.
3. The exchangeable optics system of claim 2, wherein the exchangeable optic comprises a wavefront guided optic and the primary optic provides base optical power.
4. The exchangeable optics system of claim 2, further comprising:
- a second set of fiducials on the exchangeable optic.
5. The exchangeable optics system of claim 1, wherein the one or more couplers comprises a magnetic ring on the main structure.
6. The exchangeable optics system of claim 1, wherein the one or more couplers releasably coupling the therapeutic to the intraocular base comprises magnetic material on a haptic of the supporting structure or a magnetic ring on the supporting structure.

* * * * *